

Uncontrolled document as of November 3, 2009. Refer to website for up to date specifications.

CASES 1400 Case



1400 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel padlock protectors
- Comfortable rubber over-molded handle
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence

1400 Case Configurations

Cat. #	Description
1400	1400 Case
1400NF	1400 Case (No foam)



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1400 Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
13.37" x 11.62" x 6.00" (33.9 x 29.5 x 15.2 cm)	11.81" x 8.87" x 5.18" (30 x 22.5 x 13.2 cm)	
Lid Depth	Bottom Depth	Total Depth
1.18" (3 cm)	4.00" (10.2 cm)	5.18" (13.2 cm)
Weight with foam	Weight without foam	Buoyancy Max.
4.41 lbs. (2 kg)	3.97 lbs. (1.8 kg)	20.06 lbs. (9.1 kg)
Range Temperature		
-40 / 210° F (-40 / 99° C)		

Personalized Nameplate Available

1400 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1400 Case Accessories

Cat. #	Description	Sug. Retail
1400IP	Instapak Quick® RT	US\$40.95
1400PF	Special Application Panel Frame	US\$21.95
1401	3 pc. Replacement Foam Set	US\$36.25
1403	Replacement O-ring	US\$4.60

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com