

Uncontrolled document as of December 2, 2009. Refer to website for up to date specifications.

CASES 1470 Case



1470 Case

- Double safety locking latches with keys
- Open cell core with solid wall design - strong, light weight
- Automatic Pressure Equalization Valve
- O-ring seal
- Comfortable rubber over-molded handle
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- **Watertight, crushproof, and dust proof**

1470 Case Configurations

Cat. #	Description
1470	1470 Case
1470NF	1470 Case (No foam)



Black



Desert Tan

1470 Case Specifications

Exterior Dimensions (L x W x D)

16.68" x 13.06" x 4.37" (42.4 x 33.2 x 11.1 cm)

Lid Depth

1.37" (3.5 cm)

Weight with foam

5.51 lbs. (2.5 kg)

Range Temperature

-40 / 210° F
(-40 / 99° C)

Interior Dimensions (L x W x D)

15.62" x 10.43" x 3.75" (39.7 x 26.5 x 9.5 cm)

Bottom Depth

2.37" (6 cm)

Total Depth

3.74" (9.5 cm)

Weight without foam

4.28 lbs. (1.94 kg)

Buoyancy Max.

24.91 lbs.
(11.3 kg)

Personalized Nameplate Available

1470 Case Certificates

• IP57 • MIL C-4150J

1470 Case Accessories

Cat. #	Description	Sug. Retail
1470PF	Special Application Panel Frame	US\$21.95
1471	3 pc. Replacement Foam Set	US\$28.95
1472	Shoulder Strap	US\$15.50
1473	Replacement O-ring	US\$4.50

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com